


SIMOTICS XP 1MD5 motor series

Dimensional drawings



Frame size	No. of poles	Flange with through hole (FF) /tapped hole (FT) acc. to EN 50347	Dimension designation acc. to IEC							
			LA	E	M	N	P	S	T	Z
SIMOTICS XP										
71 B	2, 4	FF130 FT85	10	30	130	110	160	9.5	3.5	4
			15	30	85	70	105	M6	2.5	4
80 B	2, 4	FF165 FT100	10	40	165	130	200	11.5	3.5	4
			15	40	100	80	120	M6	3	4
90 L	2, 4	FF165 FT115	10	50	165	130	200	11.5	3.5	4
			10	50	115	95	140	M8	3	4
100 L	2, 4	FF215 FT130	11	60	215	180	250	14	4	4
			10	60	130	110	160	M8	3.5	4
112 M	2, 4	FF215 FT130	11	60	215	180	250	14	4	4
			10	60	130	110	160	M8	3.5	4
132 S	2, 4	FF265	12	80	265	230	300	14	4	4
132 M	2, 4	FF265	12	80	265	230	300	14	4	4
160 M	2, 4, 6	FF300	20	110	300	250	350	18	5	4
160 L	2, 4, 6	FF300	20	110	300	250	350	18	5	4
180 M	2, 4, 6	FF300	16	110	300	250	350	18	5	4
180 L	2, 4, 6	FF300	16	110	300	250	350	18	5	4
200 L	2, 4, 6	FF350	20	110	350	300	400	18	5	8
225 S	2 4, 6	FF400	16	110 140	400	350	450	18	5	8
225 M	2 4, 6	FF400	16	110 140	400	350	450	18	5	8
250 M	2, 4, 6	FF500	18	140	500	450	550	18	5	8
280 S	2, 4, 6	FF500	18	140	500	450	550	18	5	8
280 M	2, 4, 6	FF500	18	140	500	450	550	18	5	8
315 S	2 4, 6	FF600	22	140 170	600	550	660	24	6	8
315 M	2 4, 6	FF600	22	140 170	600	550	660	24	6	8
315 LL	2 4, 6	FF600	22	140 170	600	550	660	24	6	8
315 L	2 4, 6	FF600	22	140 170	600	550	660	24	6	8
355 M	2 4, 6	FF740	25	140 210	740	680	800	24	6	8